



## TECHNICAL DATA SHEET – DIGITAL PRINTING – BANNER FRONT 2V3 S

420- $\mu$ m, PVC-coated, polyester banner, suitable for standard solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish.

### **BANNER FEATURES:**

|                                  | <u>Average values</u> | <u>Standard</u>   |
|----------------------------------|-----------------------|-------------------|
| • Total thickness ( $\mu$ m):    | 420                   |                   |
| • Total weight ( $g/m^2$ ):      | 510                   |                   |
| • Yarn/weft thread (DTex):       | 1100 x 1100           |                   |
| • Yarn/weft tear resistance (N): | 160 / 170             | ISO 13937-2: 2000 |

### **GENERAL PRINTER COMPATIBILITIES:**

|                    | <b>Solvent</b> | <b>Eco-solvent</b> | <b>Latex</b> | <b>UV</b> |
|--------------------|----------------|--------------------|--------------|-----------|
| <b>FRONT 2V3 S</b> | ✓              | ✓                  | ✓            | ✓         |

### **USER'S INSTRUCTIONS:**

- Printing temperature range: from +18 °C to +25 °C (from 64 °F to 77 °F)
- Touch-dry at the latest 5 minutes following application depending on the printer used.
- The optimum drying time of the inks is 24 hours minimum.
- Banner assembly by high frequency (H.F.) or heat welding.

### **STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 year if it is stored in its unopened original packaging, at a temperature ranging from 18 °C to 25 °C (from 64 °F to 77 °F), with relative humidity between 40 % and 60 %.

### **DURABILITY:** (Central Europe climate)

- Vertical outdoor exposure: 1 year

### **NOTES:**

Because of the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All information released originates from laboratory measurements on a regular basis and UV ageing tests and/or vertical outdoor exposure. However, it does not constitute a binding warranty. The seller is not held accountable for indirectly related damages beyond the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Updates of our specifications are automatically available on our website at [www.hexis-graphics.com](http://www.hexis-graphics.com).